



MOTOR OIL CP 0W-30

Product Description:

MOTOR OIL CP 0W-30 is a high performance fuel saving engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a ACEA C2 specification is required and suitable for all engines which require an PSA B71 2290 performance specification.

MOTOR OIL CP 0W-30 is based on high performance 100% synthetic technology oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

MOTOR OIL CP 0W-30 exceeds the following performance criteria:

ACEA C2 **PSA B71 2312** **Ford M2C950-A** **STJLR 03.5007**
API SP **PSA B71 2302** **VWC 53035**

Suitable for use: **Fiat 9.55535-GS1** **Fiat 9.55535-DS1** **ACEA A5/B5**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-30
Density@15°C	kg/m ³	ASTM D4052	846.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	50
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.5
Viscosity Index		ASTM D2270	178
Viscosity CCS @-35°C	cP	ASTM D5293	6000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	10.4
Sulphated Ash	%Wt	ASTM D874	0.79

Product Nr: 42430

Date Superseded: 4-04-2025

Date Issued: 7-4-2025

Revision nr: 10