



FORM OIL 150

Product Description:

FORM OIL 150 is a concrete mould oil for the construction of houses, buildings, subways and bridges.

FORM OIL 150 is based on high-grade refined base oils containing non-toxic surface-active compounds and together with the bleeding water from the concrete, it provides a low interfacial surface tension, which gives a smooth surface finish.

FORM OIL 150 is ready to use, and should be applied as thin as possible on the surface.

FORM OIL 150 enables easy removal from the moulds without damaging the concrete and gives a good rust protection of the steel moulds under normal condition. Has good release characteristics and gives no discolouring of the concrete-surface and can be used where limited heated moulds are adapted.

Appliance in a thin layer, by spraying, swabbing or brushing.
Over spill must be removed.



Property	Unit	Test Method	Typical Value
ISO VG Grade			150
Density@15°C	kg/m ³	ASTM D4052	888.6
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	139.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.03
Viscosity Index		ASTM D2270	97
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-12

Product Nr: 43910
Date Superseded: 21-6-2021

Date Issued: 14-1-2025
Revision nr: 04