



ANTIFREEZE HD

Product Description:

ANTIFREEZE HD is a premium antifreeze based on Organic Additive Technology (x-OAT) that provides year-round frost and excellent corrosion, freeze and boil protection. The coolant can withstand high temperatures thanks to the increased oxidation stability and compensates the negative effects of potential flux contamination.

ANTIFREEZE HD is designed to cope with the most extreme engine conditions in both passenger cars and heavy-duty applications.

ANTIFREEZE HD may *not* been used undiluted in a combustion engine.

ANTIFREEZE HD combines Ethylene Glycol as base fluid and an OAT backbone with virtually non-depleting organic corrosion inhibitors to obtain the following properties:

- Contains a neutralisation package to avoid adverse effect of flux material, used during the production process of Aluminium heat exchangers
- Prevents the formation of gels or deposits in the cooling system
- Excellent hard water stability avoiding the formation of insoluble deposits
- Superior oxidation and pH stability at high temperatures, resulting in limited amount of glycol degradation acids
- Outstanding heat transfer
- Increased service interval
- 2-EHA, nitrite and borate free technology

ANTIFREEZE HD exceeds the following performance criteria:

ASTM D3306-20
ASTM D6210
MAN 324 SNF
STJLR.03.5212
Volvo VCS-2
Komatsu 07.892

UNE 26-361-88/1
GMW 18270
MB 325.3
Claas
CAT
CASE MAT 3624

JIS K2234;2018
VW TL-774-D
Deutz DQC CB-14
AGCO
John-Deere

GB 29743.1 2014/2022
VW TL-774-F
Ford WSS-M97B44-D
DAF
Detroit DFS93K217



Property	Unit	Test Method	Typical Value
Color			Pink
Density @20°C	kg/l	ASTM D5931	1.124
Ash content	% w/w	ASTM D1119	1.5
Equilibrium Boiling Point	°C	ASTM D1120	180 max
Reserve Alkalinity		ASTM D1121	5.3
Initial crystallisation (40vol%)	°C	ASTM D1177	<-24
Initial crystallisation (50vol%)	°C	ASTM D1177	<-36
Initial crystallisation (60vol%)	°C	ASTM D1177	<-53

Product Nr: 45184

Date Superseded: -

Date Issued: 28-07-2025

Revision nr: -